



# ELF HTX 976

## SAE 50

*Synthetic lubricant for 2-stroke competition engines*



**"Probably the best 2-stroke lubricant in the world for high speeds."**

### Uses

- **ELF HTX 976** is a lubricant specially developed for 2-stroke competition engines used exclusively in a blend with leaded or unleaded petrol.
- **ELF HTX 976** provides optimum protection against gripping and pinking.
- **ELF HTX 976** is used for the following applications:
  - 2-stroke leaded and unleaded petrol engines running at high speeds (up to 18,000 rpm).
- **ELF HTX 976** is used with complete satisfaction by the major teams in the 250cc and 125cc Motorcycle World Championship and many Kart and Superkart drivers.
- **ELF HTX 976** is perfectly suited to competitions in:
  - Motorcycle
  - Kart
  - Superkart

### Characteristics

	Typical values	Units	Methods
Density at 15°C	0.9185	g/ml	ASTM D-1298
Viscosity at 40°C	151.6	mm <sup>2</sup> /s	ASTM D-445
Viscosity at 100°C	17.88	mm <sup>2</sup> /s	ASTM D-445
Viscosity Index	131	mPa.s	ASTM D-4741
Flash point	208	°C	ASTM D-92
Pour point	-30	°C	ASTM D-97
Cinders	< 0.15	% mass	ASTM D-874
Colour	Blue	-	Visual



## Synthetic lubricant for 2-stroke competition engines

### Properties

CHARACTERISTICS	→	TECHNICAL GAINS	→	ENGINE BENEFITS
<b>100% synthetic</b> components	→	Excellent combustion action: <b>less deposits</b>	→	Excellent reading of pistons No deterioration in engine power
Specific polymers with low cinder levels	→	Keeps <b>combustion chamber</b> clean	→	Less risk of pinking
Specific <b>demulsifiers</b>	→	Excellent <b>anti-emulsion</b> property	→	Simpler carburetion reading, even when driving in rain
Perfect <b>stability</b> at high temperatures	→	Cleanliness of <b>segmentation</b> maintained	→	Gives maximum performance at high and very high speeds

### Recommendations

- **ELF HTX 976** works perfectly up to 18,000 rpm.
- To fully benefit from the technical gains provided by **ELF HTX 976**, we do not recommend mixing it with another lubricant.
- **ELF HTX 976** is technically compatible for use with speedboats but specific rules must be followed.
- Please consult us before any use in individual lubrication.

### Storage

To preserve its original properties, **ELF HTX 976** must be handled and stored away from extreme weather conditions. The can must be carefully closed again after each use.